





THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF VTE INCORPORATED. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF VTE INCORPORATED IS PROHIBITED. VTE MAKES NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE SUITABILITY OF A PRODUCT FOR ANY INTENDED USE. THE CUSTOMER SHALL BEAR THE SOLE RESPONSIBILITY OF DETERMINING THE SUITABILITY OF ANY VTE PRODUCT FOR ITS END USE.

| LTR. | REVISIONS                        | DATE    | INT. |
|------|----------------------------------|---------|------|
| △    | REDRAWN AND UPDATED FROM 9/20/99 | 5-20-22 | RAS  |



SCALE FACTOR : NONE  
ALL DIMENSIONS GIVEN AS: in [mm]  
TOLERANCES UNLESS OTHERWISE SPECIFIED :  
MOLDED PARTS: ±.030" [±0.8mm]  
ALL ANGLES ARE ± 1 DEGREE

|                             |                       |
|-----------------------------|-----------------------|
| MATERIAL PART NO:           | 1101900102            |
| MATERIAL:                   | PVC                   |
| VENDOR PART NO:             | 9812-95-RED 683       |
| SHORE DUROMETER:            | "A" 10 SEC. 95        |
| SPECIFIC GRAVITY:           | 1.49                  |
| ULT. ELONGATION %:          | 200                   |
| MELTING TEMP:               | 345-365 F [174-185 C] |
| TENSILE STRENGTH PSI:       | 2100                  |
| DIELECTRIC STRENGTH, V./mil | 438                   |
| U.L. RATING:                | V2                    |

|                                                                                       |                 |                                                                                                                                                         |               |
|---------------------------------------------------------------------------------------|-----------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|---------------|
|  |                 | <b>VTE Incorporated</b><br>5437 Robinson Road, P.O. Box 790<br>Pellston, Michigan 49769<br>Telephone: 1-800-527-9256, 231-539-8000<br>FAX: 231-539-0914 |               |
|                                                                                       |                 | REF:                                                                                                                                                    | DATE: 5-20-22 |
| TITLE: OFFSET TERMINAL INSULATOR                                                      |                 |                                                                                                                                                         |               |
| MATERIAL: PVC                                                                         |                 | PART NO.                                                                                                                                                |               |
| COLOR: RED                                                                            | DRG CLASS REV A | 454D9V02                                                                                                                                                |               |